

**Intelligent Integration of a Vibration Sensor Allowing Synchronization to Application.** 



# <sup>D</sup>ulsarlube Mi

# Features & Advantages

Vibration Sensor	Lubricator operates only when vibration is detected on the installed application
Cost Savings	Substantial savings from the use of replaceable grease pouches and battery packs (Service Pack)
Easy Installation	Place the magnetic vibration sensor on any flat metal surface
More Reliable & Precise Lubrication	A pre-set amount of grease is delivered only when the equipment is in operation, avoiding the possibility of over lubrication and waste

# Other

Easy to adjust dispensing periods in operation Easy to install in hazardous & confined areas

## Features

Transparent container for easy visual inspection of remaining lubricant

# **Typical Industries and Applications**



 Motors and pumps from municipal water & waste water treatment facilities

Paper mills, steel mills and cement plants where water & excessive contaminants exist

Electric motors, pumps, blowers and fans

Applications where synchronized lubricators cannot be wired to an external power supply or PLC

Exclusive Distributor

# Overview



Pouch Grease Pouch

Connecting Thread PT 3/8" Male

# **Product Specifications**

## **Grease Pouch Capacity**

60ml / 125ml / 250ml (capacity setting available)

## **Power Supply**

DC 4.5V Battery Pack (replaceable) Standard : Alkaline Battery **Optional : Lithium Battery** 

**Operating Pressure** 30 ~ 60bar (435 ~ 870psi)

## **Operating Temperature**

Standard Alkaline Battery : -15°C ~ 60°C (5°F ~ 140°F) **Optional Lithium Battery :** -40°C ~ 60°C (-40°F ~ 140°F)

**Dispensing Periods** 

1~12 month

**Single Point Remote Installation** 

Max. 1m (3.3ft) with Ø6 tube

**Multi-Point Installation** 

Max. 1m (3.3ft) with Ø6 tube (Up to 2 lube points)

**Dispensing Volume Size** 0.34ml/stroke (@20°C/68°F)

**Product Certifications & IP Code** CE

## Vibration Detector

Piezoelectric Cantilever-type Film Sensor Adjustable Sensitivity Range Connection Wire Length : 1.2m

Service Life of Battery Pack 60ml / 125ml : Up to 2 years

250ml : Up to 1 year 6 months

**Product Dimensions** 183mm (H) x 91mm (Ø) \*Excludes Vibration Sensor

